Page 2

Application No: 10/695,466

Docket No.: Q128-US2

IN THE CLAIMS

RECEIVED

NOV 0 9 2006

CENTRAL FAX CENTER

Please amend the claims as follows:

1.-10. (canceled)

11. (currently amended) An energy storage device device, comprising:

a case having an opening;

an electrode assembly <u>in disposed within</u> the case, the electrode assembly including <u>electrodes</u>, the electrodes including one or more <u>at least a</u> positive <u>electrodes</u> and <u>one or more negative electrodes</u> a negative electrode including one or more negative electrodes.

a cover <u>configured</u> disposed to cover the opening of the case and defining a hole,
the cover being made of <u>aluminum</u> <u>aluminum</u>, and
the cover being electrically connected to one of the <u>electrodes</u>
electrode members of the electrode assembly; and

a disk-shaped plug configured disposed to seal the hole,

the plug being made of aluminum <u>including aluminum,</u> and

the plug being electrically connected to the cover,

the plug further having a layer of a material second metal or metal alloy other than aluminum formed on a top surface thereof of the plug.

the material being a metal or a metal alloy, and

the layer being in electrical communication with the electrically connected to the aluminum included in the cover so as to form a terminal of the energy storage device.

- 12. (currently amended) The energy storage device of claim 11, wherein the <u>layer of material second metal or metal alloy</u> has a melting point higher than the melting point of aluminum.
- 13. (currently amended) The energy storage device of claim 11, wherein the <u>layer of material second metal or metal alloy</u> is selected from the group consisting of nickel, stainless steel, titanium, copper, and alloys thereof.

Application No: 10/695,466

Docket No.: Q128-US2

Page 3

- 14. (currently amended) The energy storage device of claim 11, wherein the <u>layer of</u> material second metal or metal alloy layer is in accordance with a layer deposited on the formed by deposition over the top surface of the plug aluminum.
- 15. (currently amended) The energy storage device of claim 11, wherein the <u>layer of material second metal or metal alloy layer</u> is <u>a metal cladding on a clad formed within a recess of the top surface of the plug aluminum</u>.

16.-27. (canceled)

- 28. (currently amended) The energy storage device of claim 11, wherein the layer of material is in accordance with a layer deposited on the top surface of the aluminum.
- 29. (currently amended) The energy storage device of claim 11, wherein the layer of material is a metal cladding on the top surface of the aluminum.